Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- 1. (Currently amended) A heat exchanger, in particular a charge-air/coolant radiator (1), with a disk structure having a plurality of disks (2), two adjacent disks (2) defining an intermediate space through which a heat transfer medium flows, and having in each case one heat transfer medium inlet (9) and heat transfer medium outlet (11), eharacterized in that at wherein least two heat transfer medium ducts (5, 6) are provided per heat transfer medium inlet and/or outlet (9, 11 respectively).
- 2. (Currently amended) The heat exchanger as claimed in claim 1, characterized in that wherein the heat transfer medium ducts (5, 6) run perpendicular to the plane of the disks (2).
- 3. (Currently amended) The heat exchanger as claimed in elaim 1 or 2, characterized in that claim 1, wherein the disks (2) are of axially symmetrical design, based on their longitudinal axis, with regard to the heat transfer medium ducts (5, 6).
- 4. (Currently amended) The heat exchanger as claimed in one of the preceding claims, characterized in that claim 1, wherein disks (2) are of axially symmetrical design, based on their transverse axis, with regard to the heat transfer medium ducts (5, 6).
- (Currently amended) The heat exchanger as claimed in one of the preceding claims, eharacterized in that claim 1, wherein the heat transfer medium inlet (9) and/or the heat transfer medium outlet (11) has a branching section (7) or converging section (10).

- 6. (Currently amended) The heat exchanger as claimed in claim 5, characterized in that wherein the branching section and/or converging section (7, 10 respectively) are designed in the form of an arc of a circle.
- 7. (Currently amended) The heat exchanger as claimed in one of claims 5 and 6, eharacterized in that claim 5, wherein a bend of 30° to 90°, as seen in the flow direction, is provided in the region of the branching section (7) and/or converging section (10).
- 8. (Currently amended) The heat exchanger as claimed in one of claims 5 to 7, eharacterized in that claim 5, wherein the heat transfer medium inlet (9) which merges into two heat transfer medium ducts (5) after the branching section (7) runs parallel to the heat transfer medium ducts (5), while the bipartite part of the branching section (7) is arranged in a plane which is perpendicular to said heat transfer medium ducts (5).
- 9. (Currently amended) The heat exchanger as claimed in one of claims 5 to 8, characterized in that claim 5, wherein the heat transfer medium outlet (11) which merges from two heat transfer medium ducts (6) into the converging section (10) runs parallel to the heat transfer medium ducts (6), while the bipartite part of the branching section (7) is arranged in a plane which is perpendicular to said heat transfer medium ducts (6).
- 10. (Currently amended) The use of a heat exchanger as claimed in one of claims 1 to 9 claim 1 as a charge-air/coolant radiator (1) or oil cooler.